



INPUTS

NORMAL

2
1
PH INPUT JACKS 068270

VIBRATO

2
1

- MASTER VOLUME PUSH-PULL SWITCH DESIGNATED "MVS" SHOWN IN "OUT" POSITION, PUSH IN FOR PUSH SOUND.
- DLN0E TYPICAL 802 SIGNAL REQUIRED FOR 10 WATT OUTPUT AND 1500 MAX REVERSE INPUT COIL DRN.E.
- SIX DIGIT NUMBERS ARE FINDER PART NUMBERS.
 - ALL CAPACITORS AT LEAST 600V, M.V.D.C.
 - ALL RESISTORS 1/2 WATT ±10%.
 - VOLTAGES READ TO GROUND WITH V.T.X.M. NO SIGNAL, V5 (ONLY) VOLTAGES READ WITH "SPEED & INTENSITY" MAX, & VIBRATO ON.

CAUTION:
 100 VOLTS AVAILABLE - DISCONNECT POWER SUPPLY AND ALLOW AT LEAST 30 SECONDS FOR VOLTAGES TO BLEND OFF, BEFORE SERVICING AMPLIFIER.

100 TO 260 V
 EXPORT VERSIONS
 ONLY (50/60 Hz)

VIBRATO REV	61.6GC (4)
6L6GC (4)	61.6GC (4)
6X4 REV	6X4 REV
6X4 REVERSE	6X4 REVERSE
6X4 REV	6X4 REV
USE ON	

Finder/Rhodes/Rhodes

135 WATT 15 RMS AMP
 W/REVERSE AND VIBRATO

PART NO. 013694